

External Micrometer :

- Carbide tipped measuring faces parallel, ground and lapped.
- Stainless Steel spindle for rust prevention.
- A built-in Ratchet in the Thimble facilitates single-hand operation.
- Zero setting once done cannot be easily tampered with.
- Heat insulating grip plates cover the entire handling portion of the micrometer frame.
- Robust design withstands toughest workshop conditions.
- Sharp laser markings for better visibility & durability.

Range & Readings:

0 to 2000 mm (Reading 0.01mm)

0 to 80" (Reading 0.001")

0 to 150 mm (Reading 0.001mm)

0 to 6" (Reading 0.0001")



50 - 75 mm (2 - 3 inch)



75 - 100 mm (3 - 4 inch)



75 - 100 mm (3 - 4 inch)



100 - 125 mm (4 - 5 inch)

Technical Data Sheet

Metric :

Inch :

Type	Measuring Range	Reading
MM 25-1	0-25 mm	0.001 mm
MM 50-1	25-50 mm	
MM 75-1	50-75 mm	
MM 100-1	75-100 mm	
MM 125-1	100-125 mm	
MM 150-1	125-150 mm	
MM 25	0-25 mm	0.01 mm
MM 50	25-50 mm	
MM 75	50-75 mm	
MM 100	75-100 mm	
MM 125	100-125 mm	
MM 150	125-150 mm	
MM 175	150-175 mm	
MM 200	175-200 mm	
MM 300	200-300 mm	
MM 400	300-400 mm	
MM 500	400-500 mm	
MM 600	500-600 mm	
MM 700	600-700 mm	
MM 800	700-800 mm	
MM 900	800-900 mm	
MM 1000	900-1000 mm	
MM 1200	1000-1200 mm	
MM 1400	1200-1400 mm	
MM 1600	1400-1600 mm	
MM 1800	1600-1800 mm	
MM 2000	1800-2000 mm	

Type	Measuring Range	Reading
IN 1-1	0-1 inch	0.0001 inch
IN 2-1	1-2 inch	
IN 3-1	2-3 inch	
IN 4-1	3-4 inch	
IN 5-1	4-5 inch	
IN 6-1	5-6 inch	
IN 1	0-1 inch	0.001 inch
IN 2	1-2 inch	
IN 3	2-3 inch	
IN 4	3-4 inch	
IN 5	4-5 inch	
IN 6	5-6 inch	
IN 7	6-7 inch	
IN 8	7-8 inch	
IN 12	8-12 inch	
IN 16	12-16 inch	
IN 20	16-20 inch	
IN 24	20-24 inch	
IN 28	24-28 inch	
IN 32	28-32 inch	
IN 36	32-36 inch	
IN 40	36-40 inch	
IN 44	40-44 inch	
IN 48	44-48 inch	
IN 52	48-52 inch	
IN 56	52-56 inch	
IN 60	56-60 inch	